

Model		DCS-930L	DCS-5030L	DCS-5222L	DCS-936L	DCS-960L	DCS-8200LH	DCS-2630L	DCS-2530L	DCS-6010L
產品圖										
畫素		30萬	100萬	100萬	100萬	100萬	100萬	200萬	200萬	200萬
旋轉鏡頭		-	水平340度 垂直110度	水平340度 垂直120度	-	-	-	-	-	-
可視角度(水平 / 垂直)		45.3° / 34.5°	94.36° / 59.3°	98° / 52°	112° / 77°	180° / 120°	180° / 120°	180° / 112°	180° / 86°	180° / 180°
數位放大		4倍	4倍	10倍	4倍	8倍	8倍	8倍	10倍	10倍
影像壓縮格式		M-JPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/M-JPEG/MPEG4
網路		有線/無線	有線/無線	有線/無線	無線	無線802.11AC	無線802.11AC	無線802.11AC	無線	有線/無線
WPS		O	O	O	O	O	O	O	O	O
夜視功能		-	5米夜視	8米夜視	5米夜視	5米夜視	5米夜視	5米夜視	5米夜視	-
PIR(紅外線人體感測)		-	-	O	-	-	-	O	-	-
單向語音/雙向語音		單向語音	單向語音	雙向對講	單向語音	單向語音	單向語音	雙向對講	單向語音	雙向對講
移動偵測		O	O	O	O	O	O	O	O	O
聲音偵測		O	O	O	O	O	O	O	O	-
內建麥克風		O	O	O	O	O	O	O	O	O
外接麥克風		-	-	O	-	-	-	-	-	-
內建喇叭		-	-	O	-	-	-	O	-	O
外接喇叭		-	-	O	-	-	-	-	-	-
microSD插槽(事件錄影)		-	O	O	O	O	O	O	O	O
支援記憶卡容量		-	128G	128G	128G	128G	128G	128G	128G	32G
app簡易設定		O	O	O	O	O	O	O	O	O
	mydlink Home app	-	-	-	-	-	O	-	-	-
	mydlink lite app	O	O	O	O	O	-	O	O	O
	mydlink app	O	O	O	O	O	-	O	O	O
雲錄影		-	-	-	-	-	-	-	-	-
變壓器規格		輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1A	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.5A	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2.5A	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.2A
ONVIF		-	-	O	-	-	-	-	O	O
D-ViewCam免費管理軟體 (DCS-100)		O	-	O	-	-	-	-	-	O
mydlink NVR		DNR-202L/ DNR-312L/ DNR-322L	-	DNR-202L/ DNR-312L/ DNR-322L	DNR-202L/ DNR-312L/ DNR-322L	DNR-202L/ DNR-312L/ DNR-322L	-	DNR-202L/ DNR-312L/ DNR-322L	DNR-202L/ DNR-312L/ DNR-322L	DNR-202L/ DNR-312L/ DNR-322L
WEB UI(網頁管理介面)		O	O	O	O	O	-	O	O	O

