













Model		DCS-6010L	DCS-8000LH	DCS-8000LHV2	DCS-8100LH	DCS-8010LH	DCS-8300LH	DCS-8330LH	DCS-8515LH	DCS-8525LH	DCS-8526LH
產品圖											
畫素		200萬	100萬	200萬	100萬	100萬	200萬	200萬	100萬	200萬	200萬
旋轉鏡頭		-	-	-	-	-	-	-	水平340度 垂直105度	水平340度 垂直110度	水平340度 垂直100度
可視角度(水平 / 垂直)		180° / 180°	112° / 54°	113° / 58°	180° / 80°	96° / 53°	137° / 71°	126° / 63°	96° / 53°	98° / 52°	120° / 60°
數位放大		10倍	4倍	支援數位變焦	4倍	支援數位變焦	支援數位變焦	支援數位變焦	支援數位變焦	支援數位變焦	支援數位變焦
影像壓縮格式		H.264/M-	H.264	H.264	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264	H.264	H.264	H.264
網路		有線/無線	無線	無線	無線	無線	無線	無線	無線	有線/無線	有線/無線
WPS		O	-	-	-	-	-	-	-	-	-
夜視功能		-	5米夜視	5米夜視	5米夜視	5米夜視	5米夜視	5米夜視	5米夜視	5米夜視	5米夜視
單向語音/雙向語音		雙向對講	單向語音	單向語音	雙向對講	單向語音	雙向對講	雙向對講	雙向對講	雙向對講	雙向對講
移動偵測		O	O	O人體偵測	O	O	O	O 人體偵測、 、多區域偵測/電子圍籬/ 優先區域偵測功能	O	O	O人體偵測
聲音偵測		-	O	O	O	O	O	O	O	O	O
內建麥克風		O	O	O	O	O	O	O	O	O	O
內建喇叭		O	-	-	O	-	O	O	O	O	O
microSD插槽(事件錄影)		O	-	-	O	O	O	O	O	O	O
支援記憶卡容量		32G	-	-	256G	256G	256G	256G	256G	256G	256G
戶外認證		-	-	-	-	-	-	-	-	-	-
app簡易設定		O	O 藍牙設定	O 藍牙設定	O 藍牙設定	O 藍牙設定	O 藍牙設定	O 藍牙設定	O 藍牙設定	O 藍牙設定	O 藍牙設定
	mydlink lite app	O	O*A1	-	O*A1	-	-	-	-	-	
	mydlink app	O	O*A2	O	O*A2	O	O	O	O	O	O
mydlink 入口網站即時監看		O	O	O	O	O	O	O	O	O	O
雲錄影		-	O*A2	O	O*A2	O	O	O	O	O	O
變壓器規格		輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.2A	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 1.2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A (Micro-USB)	輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A (Micro-USB)
ONVIF		O	-	ONVIF Profile S	-	-	-	ONVIF Profile S	-	-	ONVIF Profile S
Zigbee3.0		-	-	-	-	-	-	O	-	-	-
google助理 / alexa		O	O	O	O	O	O	O	O	O	O
D-ViewCam免費管理軟體		O	-	-	-	-	-	-	-	-	-
WEB UI(網頁管理介面)		O	O	O	O	O	O	O	O	O	O

*DCS-8000LH/A1與DCS-8100LH/A1請更新韌體至v2.00方可支援雲錄影功能

DCS-8600LH

200萬
-
117° / 59°
支援數位變焦
H.264
無線
-
7米夜視
雙向對講
O
O
O
O
O
256G
IP65
O 藍牙設定
-
O
O
O
輸入: 100 ~ 240 VAC 輸出: 5VDC/ 2A
-
-
O
-
O